

## 32" x 48" Rectangular Shower Ensembles

DURAWALL® Shower Walls, DURABASE® Shower Floors & STYLEMATE® Enclosures



The dramatic look of a premium-quality shower ensemble from E.L. Mustee & Sons, Inc., is the proven way to transform any bathroom space into something very special.

Mustee's 48" wide rectangular shower ensembles are created using a DURABASE® shower floor, DURAWALL® shower walls and a STYLEMATE® enclosure. The 48" rectangular shower ensemble is perfect for anyone looking to create a dramatic, king-size shower space.

### Features:

- High quality, molded-fiberglass construction provides years of service.
- DURAWALL® panels feature a sturdy, watertight tongue-and-groove design in addition to three large, molded-in shelves.
- Mounts direct-to-stud with mounting flanges hidden behind drywall or other wall treatment.
- STYLEMATE® By-Pass enclosure with tempered safety glass.
- DURABASE® fiberglass shower floors are strong, stable and feature a slip-resistant Starburst® floor surface design.
- All surfaces are mold/mildew resistant, easy to clean, with a deep-gloss finish.


### Code Accepted:

Fiberglass Shower Ensembles meet or exceed performance requirements:

- American Society of Testing and Material (ASTM) — D 635, E 84 and E 162
- American National Standards Institute (ANSI) — Z 124.1.2 and Z 97.1
- IAPMO® as indicated 
- Warnock Hersey® as indicated 

### Specifications


**General:** Furnish and install per plans, 32" x 48" rectangular, manufactured by E.L. Mustee & Sons, Inc., consisting of:



### DURAWALL® SHOWER WALL

Model	Color
748-32WHT	White
748-32BN	Bone


**DURAWALL® Shower Wall** — Model: \_\_\_\_\_ shall be semi-gloss, 3-piece wall. Panels are molded fiberglass, using matched metal molds under extreme heat and pressure with a minimum uniform thickness of 125 mils and mount direct-to-studwalls. Includes center panel and two side panels with three molded-in shelves. Self-aligning panels using a tongue-and-groove connection. Shall meet ANSI Specification Z 124.1.2. Color: \_\_\_\_\_ (White, Bone).



### DURABASE® SHOWER FLOOR

Model	Color
3248M	White
3248BN	Bone

**DURABASE® Shower Floor** — Model: \_\_\_\_\_ floor to be one-piece, molded fiberglass, made with matched metal molds. Surface to be slip-resistant Starburst® design that does not interfere with the flow of water. Size 48" x 32". Shoulder will be no less than 3" high or less than 1" wide. Tiling flange will extend not less than 1" higher than the threshold which provides an integral molded water barrier. Threshold will be not less than 4 1/2" high. Molded-in drain and drain seal for installation of 2" iron DWV (Sch. 40) PVC or ABS sanitary drain pipe. Removable strainer. Shall meet ANSI Specification Z 124.1.2. Color: \_\_\_\_\_ (White, Bone).



### STYLEMATE® ENCLOSURE

Model	Finish/Type Glass
48.401	Chrome/Clear w/Stripes
48.403	Chrome/Clear
48.404	Brushed Nickel/Clear
48.405	Oil-Rubbed Bronze/Clear
<i>Frameless design</i>	
48.406	Chrome/Clear
48.407	Brushed Nickel/Clear
48.408	Oil-Rubbed Bronze/Clear

**STYLEMATE® By-Pass Enclosure** — Model \_\_\_\_\_ fits 47" opening. Shall be a By-Pass style door with a \_\_\_\_\_ (Chrome, Brushed Nickel, Oil-Rubbed Bronze) finish aluminum frame and clear tempered safety glass. Out-of-plumb conditions up to 1" can be adjusted. Shall meet ANSI Specification Z 97.1.

## 34" x 48" Rectangular Shower Ensembles

DURAWALL® Shower Walls, DURABASE® Shower Floors & STYLEMATE® Enclosures



The dramatic look of a premium-quality shower ensemble from E.L. Mustee & Sons, Inc., is the proven way to transform any bathroom space into something very special.

Mustee's 48" wide rectangular shower ensembles are created using a DURABASE® shower floor, DURAWALL® shower walls and a STYLEMATE® enclosure. The 48" rectangular shower ensemble is perfect for anyone looking to create a dramatic, king-size shower space.

### Features:

- High quality, molded-fiberglass construction provides years of service.
- DURAWALL® panels feature a sturdy, watertight tongue-and-groove design in addition to three large, molded-in shelves.
- Mounts direct-to-stud with mounting flanges hidden behind drywall or other wall treatment.
- STYLEMATE® By-Pass enclosure with tempered safety glass.
- DURABASE® fiberglass shower floors are strong, stable and feature a slip-resistant Starburst® floor surface design.
- All surfaces are mold/mildew resistant, easy to clean, with a deep-gloss finish.


### Code Accepted:

Fiberglass Shower Ensembles meet or exceed performance requirements:

- American Society of Testing and Material (ASTM) — D 635, E 84 and E 162
- American National Standards Institute (ANSI) — Z 124.1.2 and Z 97.1
- IAPMO® as indicated 
- Warnock Hersey® as indicated 

### Specifications

**General:** Furnish and install per plans, 34" x 48" rectangular, manufactured by E.L. Mustee & Sons, Inc., consisting of:




### DURAWALL® SHOWER WALL

Model	Color
748-34WHT	White
748-34BN	Bone



**DURAWALL® Shower Wall** — Model: \_\_\_\_\_ shall be semi-gloss, 3-piece wall. Panels are molded fiberglass, using matched metal molds under extreme heat and pressure with a minimum uniform thickness of 125 mils and mount direct-to-studwalls. Includes center panel and two side panels with three molded-in shelves. Self-aligning panels using a tongue-and-groove connection. Shall meet ANSI Specification Z 124.1.2. Color: \_\_\_\_\_ (White, Bone).




### DURABASE® SHOWER FLOOR

Model	Color
3448M	White
3448BN	Bone



**DURABASE® Shower Floor** — Model: \_\_\_\_\_ floor to be one-piece, molded fiberglass, made with matched metal molds. Surface to be slip-resistant Starburst® design that does not interfere with the flow of water. Size 48" x 34". Shoulder will be no less than 3" high or less than 1" wide. Tiling flange will extend not less than 1" higher than the threshold which provides an integral molded water barrier. Threshold will be not less than 4 1/2" high. Molded-in drain and drain seal for installation of 2" iron DWV (Sch. 40) PVC or ABS sanitary drain pipe. Removable strainer. Shall meet ANSI Specification Z 124.1.2. Color: \_\_\_\_\_ (White, Bone).



### STYLEMATE® ENCLOSURE

Model	Finish/Type Glass
48.401	Chrome/Clear w/Stripes
48.403	Chrome/Clear
48.404	Brushed Nickel/Clear
48.405	Oil-Rubbed Bronze/Clear

Frameless design

48.406	Chrome/Clear
48.407	Brushed Nickel/Clear
48.408	Oil-Rubbed Bronze/Clear

**STYLEMATE® By-Pass Enclosure** — Model \_\_\_\_\_ fits 47" opening. Shall be a By-Pass style door with a \_\_\_\_\_ (Chrome, Brushed Nickel, Oil-Rubbed Bronze) finish aluminum frame and clear tempered safety glass. Out-of-plumb conditions up to 1" can be adjusted. Shall meet ANSI Specification Z 97.1.